

Ordering details for spiral staircases

Let Weland do the planning and design for the staircase. If we are given the details below, you will receive a very practical staircase. Fill in the following details or send a sketch with dimensions or an architect's drawing to place an order or for a fast quote.

Railings Standard Hoop Round bar Intermediate rail Sheet metal Mesh Glass Handrails Galvanized steel according to ZM310 with a diameter of Ø 42 mm. Galvanized steel according to ZM310 with a diameter of Ø 42 mm. Ash, Birch, Beech & Oak Inner handrail Galvanized steel according to ZM310 with a diameter of Ø 42 mm.	Stair treads Floor grating Durbar plate Perforated grip plate Grey concrete Terrazzo concrete Ash Birch Beech Oak Sheet metal for floor tiles Sheet metal for carpet Landings Square, standard 90° landing with radius Final step Customised dimensions: Dim	Protective cage Quarter-circle Protective Cage Full-circle Protective Cage Protective Cage, Stair Enclosure Surface treatment Hot dip galvanised, standard Painted, internal use Painted, external use Radius of the staircase 600 mm 700 mm 800 mm 900 mm 11000 mm 11000 mm 11000 mm 1200 mm 1300 mm 1300 mm
Storey height - Floor to floor		Other comments
 Lower landing Wall, doors, windows. Location with dimensions. Mark doors with size and swing. Upper landing Wall, doors, windows. Location with dimensions. Size of any arch opening. Mark doors with size and swing. Arch railing Mark any arch railing with dimensions. 		