

Ordering details for spiral staircase JOS

Let Weland do the planning and design for the staircase. If we are given the details below, you will receive a very practical staircase. Fill in the following details or send a sketch with dimensions or an architect's drawing to place an order or for a fast quote.

Railings

- Slit
- Square
- Round
- Solid

Handrails

Galvanized steel according to ZM310 with a diameter of \varnothing 42 mm.

Inner handrails

Galvanized steel according to ZM310 with a diameter of \varnothing 42 mm.

Stair treads

Perforated grip plate

Landings

- Square, standard
- 90° landing with radius
- Final step
- Customised dimensions:
Dim. x mm

Gates

- Lower landing
- Upper landing

Protective cage

- Quarter-circle Protective Cage
- Full-circle Protective Cage
- Protective Cage, Stair Enclosure

Surface treatment

- Hot dip galvanised, standard
- Painted, internal use
- Painted, external use


Radius of the staircase

- 800 mm
- 900 mm
- 1000 mm
- 1100 mm
- 1200 mm
- 1300 mm

Storey height - Floor to floor


Lower landing

- Wall, doors, windows. Location with dimensions.
- Mark doors with size and swing.




Upper landing

- Wall, doors, windows. Location with dimensions.
- Size of any arch opening.
- Mark doors with size and swing.



Arch railing

- Mark any arch railing with dimensions.



Other comments
